






BFS 850x850 F3 EC

- Duct fan with square connections.
- High capacity and very good efficiency.
- Impeller with backward curved blades.
- The external rotor motor has maintenance-free sealed ball-bearings and is very energy efficient.
- Speed controlling can be done with the built-in potentiometer, 0-10 V alt. external control.
- Integrated motor protection.
- Junction box has enclosure class IP 54.
- Fan housing is manufactured from galvanized sheet steel.
- The fan is intended to be installed in a duct system.
- A duct connected fan can be installed outside or in damp environments.
- Easy installation in any position.

Accessories

- Speed controller MS EC
- Controller IQ-Reg EC
- Plejd Controller
- Pressure regulator CALAIR-PR-230V
- Pressure regulator FKP-R


Voltage steps

1	2	3	4
5V	7V	8V	10V

TECHNICAL DATA

Voltage	400 V
Phase	3 ~
Frequency	50/60 Hz
Power	4690 W
Current	7.1 A
Speed	1430 r.p.m.
Max. temperature of transported air	40 °C
Sound pressure level at 3 m	65 dB(A)
Weight	66.7 kg
Enclosure class	54 IP
Insulation class, motor	F
Duct connection	850x850 mm
Max. flow @ 0Pa	22852.863988019 m³/h
Max. pressure	936 Pa
Voltage range	380-480 V

7460034
BFS 850x850 F3 EC
SOUND DATA

	Flow (m³/h)	L_{WA} tot dB (A)	63Hz	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	8KHz
4. Surrounding Lw dB(A) 10V	12701	72	54	60	69	66	64	59	53	46
4. Outlet Lw dB(A) 10V	12701	96	84	88	88	88	90	86	82	75
4. Inlet Lw dB(A) 10V	12701	91	76	80	82	82	87	84	82	76
3. Inlet Lw dB(A) 8V	11146	88	73	78	77	78	83	81	78	71
2. Inlet Lw dB(A) 7V	9295	82	67	72	72	72	77	75	72	64
1. Inlet Lw dB(A) 5V	6462	72	59	61	63	63	68	66	60	52

DIMENSIONS
